

# WEST

Help

Logout

Main Menu Search Form Result Set ShowS Numbers Edit S Numbers

First Hit

Previous Document

Next Document

Full Title Citation Front Review Classification Date Reference Claims KWIC

## Document Number 201

Entry 201 of 422

File: JPAB

Nov 24, 1992

PUB-NO: JP404335997A

DOCUMENT-IDENTIFIER: JP 04335997 A

TITLE: BOILER TUBE FOR CITY REFUSE INCINERATOR

PUBN-DATE: November 24, 1992

### INVENTOR-INFORMATION:

NAME

MORIMOTO, JUNJI

HAMAMOTO, TAKANORI

OTSUKA, TAKAO

KOYAMA, MASAHIRO

YAMADA, KATSUHIRO

TOYAMA, KAZUHIRO

### ASSIGNEE-INFORMATION:

NAME

COUNTRY

HITACHI ZOSEN CORP N/A

APPL-NO: JP03104560

APPL-DATE: May 10, 1991

INT-CL (IPC): F28F 19/06; C23C 4/08; F22B 37/04; F22B 37/10; F23G 5/46; F28F 21/08

### ABSTRACT:

PURPOSE: To obtain a boiler tube for a city refuse incinerator, having excellent wear resistance and corrosion resistance by forming an alloy film made of 15-55wt.% of Cr and the balance of Ni on an outer surface of a heat transfer tube by an explosion spraying method.

CONSTITUTION: A heat exchanger 5 is formed by aligning many heat transfer tubes 9 longitudinally between a left side wall 7 and a right side wall 8 in a lengthwise direction, and soot blowers 6 are provided on a back wall 10. A metal film 12 made of 15-55wt.% of Cr and the balance wt.% of Ni is formed on an outer periphery of part of the tube 9 group oppositely to drain vapor from the blowers 6 by an explosion spraying method. As a result, an increase in oxidation of the explosion spraying method is reduced as compared with that of a flame spraying method with lapse of time. Accordingly, the explosion spraying method can form a dense film having a high adhesive strength to provide an excellent high temperature resistance.

COPYRIGHT: (C) 1992, JPO&Japio

Main Menu Search Form Result Set ShowS Numbers Edit S Numbers

| <u>DB Name</u> | <u>Query</u>  | <u>Hit C</u> | <u>unt</u> | <u>Set Name</u> |
|----------------|---|--------------|------------|-----------------|
| ALL            | l15 same l11  | 422          |            | <u>L17</u>      |
| ALL            | l15 and l11   | 1285         |            | <u>L16</u>      |
| ALL            | corrosion resist\$4 same (chromium or Cr) same (nickel or Ni)   | 9627         |            | <u>L15</u>      |
| ALL            | corrosion resist\$4 same (chromium or cr)   | 17843        |            | <u>L14</u>      |
| ALL            | l11 same l12  | 3046         |            | <u>L13</u>      |
| ALL            | (chromium or Cr) near5 (nickel or Ni)   | 91641        |            | <u>L12</u>      |
| ALL            | (atomiz\$4 or atomis\$4 or atomization or atomisation or spray\$3)  | 486785       |            | <u>L11</u>      |
| ALL            | (atomiz\$4 or atomis\$4 or atomization or atomisation or spray\$3)<br>same (nickel or Ni) near4 (% or percent) same (chromium or<br>Cr)near\$4 (% or percent) | 0            |            | <u>L10</u>      |
| ALL            | (atomiz\$4 or atomis\$4 or atomization o atomisation) same (nickel or<br>Ni) near4 (% or percent) same (chromium or Cr)near\$4 (% or<br>percent)              | 0            |            | <u>L9</u>       |
| ALL            | (atomiz\$4 or atomis\$4 or atomization o atomisation) same (nickel or<br>Ni) same (chromium or Cr)  | 609          |            | <u>L8</u>       |
| ALL            | corrosion resist\$4 same high (chromium or Cr) content  | 131          |            | <u>L7</u>       |
| ALL            | l4 and corrosion resist\$4  | 332          |            | <u>L6</u>       |
| ALL            | l1 and corrosion resist\$4  | 1065         |            | <u>L5</u>       |
| ALL            | (chromium or Cr) near3 (40% or 40 percent) same (nickel or Ni)  | 993          |            | <u>L4</u>       |
| ALL            | (chromium or Cr) near4 (40% or 40 percent) same (nickel or Ni)  | 1189         |            | <u>L3</u>       |
| ALL            | (chromium or Cr) same (nickel or Ni) same (40% or 40 percent)   | 3111         |            | <u>L2</u>       |
| ALL            | corrosion resist\$4 same (40% or 40 percent)  | 1065         |            | <u>L1</u>       |